



50 mm x 110 mm x 27 mm skf 7310 becbm bearing

Bearing No. 7310 becbm

7310 becbm Bearing 2D drawings and 3D CAD models

Size	110x50x27 mm
Bore Diameter	110 mm
Outer Diameter	50 mm
Width	27 mm
d	50 mm
D	110 mm
B	27 mm
d ₁	73.8 mm
d ₂	61.13 mm
D ₁	88.8 mm
a	47 mm
r _{1,2} - min.	2 mm
r _{3,4} - min.	1 mm
d _a - min.	61 mm
D _a - max.	99 mm
D _b - max.	104 mm
r _a - max.	2 mm
r _b - max.	1 mm
Basic dynamic load rating - C	75 kN
Basic static load rating - C ₀	51 kN
Fatigue load limit - P _u	2.2 kN
Reference speed	8000 r/min
Limiting speed	8000 r/min
Calculation factor - k _r	0.1



PRECISION BEARING CORP.

Calculation factor - k_a	1.6
Calculation factor - e	1.14
Calculation factor - X	0.57
Calculation factor - Y_0	0.52
Calculation factor - Y_1	0.55
Calculation factor - Y_2	0.93
Calculation factor - X	0.35
Calculation factor - Y_0	0.26
Calculation factor - Y_1	
Calculation factor - Y_2	0.57
Category	Angular Contact Ball Bearings
Inventory	11.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.191
EAN	7316577086396
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Brass
Contact Angle	40 Degree
Internal Clearance	CB
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric



PRECISION BEARING CORP.

Long Description	50MM Bore; 110MM Outside Diameter; 27MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; CB; Brass Cage; 40 Degree; 1 (Single); Univers
Other Features	Normal Axial Internal Clearance
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	7310 BECBM
Outside Diameter	4.331 Inch 110 Millimeter
Width	1.063 Inch 27 Millimeter
Bore	1.969 Inch 50 Millimeter
bore diameter:	50 mm
radial static load capacity:	51 kN
outside diameter:	110 mm
cage material:	Brass
overall width:	27 mm
outer ring width:	27 mm
contact angle:	40 °
maximum rpm:	8000 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	ABEC 3 (ISO Class 6)
closure type:	Open
fillet radius:	2 mm

PRECISION BEARING CORP.

radial dynamic load capacity:	75 kN
series:	73
d_1	73.8 mm
d_2	61.13 mm
D_1	88.8 mm
$r_{1,2}$ min.	2 mm
$r_{3,4}$ min.	1 mm
d_a min.	61 mm
D_a max.	99 mm
D_b max.	104 mm
r_a max.	2 mm
r_b max.	1 mm
Basic dynamic load rating C	75 kN
Basic static load rating C_0	51 kN
Fatigue load limit P_u	2.16 kN
Calculation factor A	0.0418
Calculation factor k_r	0.1
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor Y_0	0.26
Calculation factor Y_2	0.57
Calculation factor X	0.57
Calculation factor Y_0	0.52
Calculation factor Y_1	0.55
Calculation factor Y_2	0.93
Mass bearing	1.1 kg