



40 mm x 90 mm x 23 mm skf nu 308 ecp bearing

Bearing No. nu 308 ecp

nu 308 ecp Bearing 2D drawings and 3D CAD models

Size	90x40x23 mm
Bore Diameter	90 mm
Outer Diameter	40 mm
Width	23 mm
d	40 mm
D	90 mm
B	23 mm
D <sub>1</sub>	75 mm
F	52 mm
r <sub>1,2</sub> - min.	1.5 mm
r <sub>3,4</sub> - min.	1.5 mm
s	1.4 mm
d <sub>a</sub> - min.	48 mm
d <sub>a</sub> - max.	50 mm
d <sub>b</sub> - min.	54 mm
D <sub>a</sub> - max.	81.8 mm
r <sub>a</sub> - max.	1.5 mm
r <sub>b</sub> - max.	1.5 mm
Basic dynamic load rating - C	93 kN
Basic static load rating - C <sub>0</sub>	78 kN
Fatigue load limit - P <sub>u</sub>	10.2 kN
Reference speed	8000 r/min
Limiting speed	9500 r/min
Calculation factor - k <sub>r</sub>	0.15
Category	Cylindrical Roller Bearings



## PRECISION BEARING CORP.

Inventory	5.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.669
EAN	7316577027993
Product Group	B04144
Bore Profile	Straight
Cage Material	Polymer
Precision Class	RBEC 1   ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring - Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C0-Medium
Retainer	Yes
Relubricatable	Yes
Inch - Metric	Metric
Other Features	High Capacity   Plain Inner Ring   2 Rib Outer Ring   Cage on Outer Ring ID
Long Description	40MM Bore; Straight Bore Profile; 90MM Outside Diameter; 23MM Width; Polymer Cage Material; RBEC 1   ISO P0; Single Row; Inner Ring - Both Sides Separable; No Snap Ring; Relubricatable; C0-Medium Int
Category	Cylindrical Roller Bearing
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>



## PRECISION BEARING CORP.

Manufacturer Item Number	NU 308 ECP
Weight / LBS	1.473
Width	0.906 Inch   23 Millimeter
Outside Diameter	3.543 Inch   90 Millimeter
Bore	1.575 Inch   40 Millimeter
bore diameter:	40 mm
precision rating:	RBEC 1 (ISO Class Normal)
outside diameter:	90 mm
maximum rpm:	9500 RPM
overall width:	23 mm
bearing material:	Steel
flanges:	(2) Outer Ring
cage material:	Polyamide
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	Open
internal clearance:	C0
application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools
ring separation:	Separable Ring
outer ring width:	23 mm
operating temperature range:	Maximum of +300 ° F
fillet radius:	1.5 mm
dynamic load capacity:	93 kN
series:	NU3
static load capacity:	78 kN
D <sub>1</sub>	75 mm
r <sub>1,2</sub> min.	1.5 mm
r <sub>3,4</sub> min.	1.5 mm



## PRECISION BEARING CORP.

s max.	1.4 mm
$d_a$ min.	48 mm
$d_a$ max.	50 mm
$d_b$ min.	54 mm
$D_a$ max.	81.8 mm
$r_a$ max.	1.5 mm
$r_b$ max.	1.5 mm
Basic dynamic load rating C	93 kN
Basic static load rating $C_0$	78 kN
Fatigue load limit $P_u$	10.2 kN
Calculation factor $k_r$	0.15
Limiting value e	0.2
Axial load factor Y	0.6
Mass bearing	0.65 kg