

PRECISION BEARING CORP.



7309 bep Bearing 2D drawings and 3D CAD models

45 mm x 100 mm x 25 mm skf 7309 bep bearing

Bearing No. 7309 bep

Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.81
EAN	7316576634215
Product Group	B00308
Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3 ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polymer
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch - Metric	Metric
Long Description	45MM Bore; 100MM Outside Diameter; 25MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
Category	Angular Contact Ball



PRECISION BEARING CORP.

	Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	7309 BEP
Weight / LBS	1.79
D	3.937 Inch 100 Millimeter
B	0.984 Inch 25 Millimeter
d	1.772 Inch 45 Millimeter
bore diameter:	45 mm
radial static load capacity:	37.5 kN
outside diameter:	100 mm
cage material:	Nylon
overall width:	25 mm
outer ring width:	25 mm
contact angle:	40 °
maximum rpm:	8000 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	Not Rated
closure type:	Open
fillet radius:	1.5 mm
radial dynamic load capacity:	55.9 kN
series:	73
d	45 mm
D	100 mm
B	25 mm
d ₁	66.5 mm
d ₂	55.25 mm

PRECISION BEARING CORP.

D_1	79.9 mm
a	43 mm
$r_{1,2}$ min.	1.5 mm
$r_{3,4}$ min.	1 mm
d_a min.	54 mm
D_a max.	91 mm
D_b max.	94.4 mm
r_a max.	1.5 mm
r_b max.	1 mm
Basic dynamic load rating C	55.9 kN
Basic static load rating C_0	37.5 kN
Fatigue load limit P_u	1.6 kN
Reference speed	8500 r/min
Limiting speed	8000 r/min
Calculation factor A	0.0268
Calculation factor k_r	0.1
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor Y_0	0.26
Calculation factor Y_2	0.57
Calculation factor X	0.57
Calculation factor Y_0	0.52
Calculation factor Y_1	0.55
Calculation factor Y_2	0.93
Mass bearing	0.82 kg