



30 mm x 62 mm x 23.8 mm skf 3206 a bearing

Bearing No. 3206 a

3206 a Bearing 2D drawings and 3D CAD models

Size	62x30x23.8 mm
Bore Diameter	62 mm
Outer Diameter	30 mm
Width	23,8 mm
d	30 mm
D	62 mm
B	23.8 mm
d ₂	38.7 mm
D ₂	55.15 mm
r _{1,2} - min.	1 mm
a	36 mm
d _a - min.	36 mm
D _a - max.	56 mm
r _a - max.	1 mm
Basic dynamic load rating - C	30 kN
Basic static load rating - C ₀	20.4 kN
Fatigue load limit - P _u	0.865 kN
Reference speed	10000 r/min
Limiting speed	10000 r/min
Calculation factor - k _r	0.06
Calculation factor - e	0.8
Calculation factor - X	0.63
Calculation factor - Y ₀	0.66
Calculation factor - Y ₁	0.78



PRECISION BEARING CORP.

Calculation factor - Y ₂	1.24
Category	Angular Contact Ball Bearings
Inventory	12.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.303
EAN	7316571185491
Product Group	B00152
Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 3 ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	25 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch - Metric	Metric
Long Description	30MM Bore; 62MM Outside Diameter; 23.8MM Width; Open; No Flush Ground; Ball Bearing; Double Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact



PRECISION BEARING CORP.

Manufacturer URL	http://www.skf.com
Manufacturer Item Number	5206 A
Weight / LBS	0.658
Width	0.937 Inch 23.8 Millimeter
Bore	1.181 Inch 30 Millimeter
Outside Diameter	2.441 Inch 62 Millimeter
bore diameter:	30 mm
radial static load capacity:	20-2/5 kN
outside diameter:	62 mm
cage material:	Metal
overall width:	0.9375 in
outer ring width:	23.8 mm
contact angle:	30 °
maximum rpm:	10000 RPM
row type & fill slot:	Double-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	Not Rated
closure type:	Open
fillet radius:	1 mm
radial dynamic load capacity:	30 kN
series:	32
d_2	38.7 mm
D_2	55.15 mm
$r_{1,2}$ min.	1 mm
d_a min.	36 mm
D_a max.	56 mm
r_a max.	1 mm
Basic dynamic load rating C	30 kN
Basic static load rating C_0	20.4 kN
Fatigue load limit P_u	0.865 kN
Calculation factor k_r	0.06



PRECISION BEARING CORP.

Calculation factor e	0.8
Calculation factor X	0.63
Calculation factor Y_0	0.66
Calculation factor Y_1	0.78
Calculation factor Y_2	1.24
Mass bearing	0.29 kg